AUTHORIZED SURGEONS

Dr. A. W. Ide, Chief Surgeon..... St. Paul.

Dr. B. I. Derauf, Dr. J. W. Jesion, Dr. L. Rosenbladt, Dr. A. McEwan, Dr. F. J. Brown, Dr. J. B. Evensta.

Assistant Surgeons, N. P. B. A. Hospital, St. Paul.

SPECIALISTS

Minneapolis.

Dr. A. G. Athens, Oculist and Aurist, 1214 Medical Arts Bldg.,

Dr. M. F. Fellows, Oculist and Aurist, 1209 Medical Arts Bldg., Duluth.

SURGEONS

Dr. A. L. Kyllo, 5719 Tower Ave., Superior Dr. W. H. Schnell, 28 Columbia Bldg., Superior Dr. F. C. Sarazin, 28 Columbia Bldg., Superior

Dr. C. H. Christiansen, Superior Dr. G. G. MacRae, 925 Med. Arts Bldg., Duluth Dr. C. M. Smith, 1115 Med. Arts Bldg., Duluth Dr. C. L. Haney, 2004 W. Superior St., Duluth

C. M. ST. P. & P. RY. SURGEONS

Dr. Cyril M. Smith, 1115 Medical Arts Bldg., Duluth Dr. M. F. Fellows, 1209 Med. Arts Bldg., Duluth

LOCATION OF STRETCHERS

East End Passenger Station. Central Avenue Freight Station. Superior Freight Station. Duluth-Fifth Avenue Switch Shanty, Dock 6, Union Depot, Store Room, Tool Car. West Duluth Passenger Station.

NOTE.

N. P. B. A. physicians and surgeons, when called upon, will attend to all cases of sickness and accident to employes, passengers, and others. In a case of illness or in any case of injury unrelated to Railway operation, surgeon should endeavor to collect a reasonable fee for service from person attended, other than members of the N. P. B. A. If unable to collect, Chief Surgeon should be notified.

Where injuries are directly related to Railway operation, charge for service should be sent to the General Claim Agent of the Railway Company.

In case of emergency, proper aid should be procured until arrival of local surgeon, when case must be placed in his hands.

INDEX

First Sub-Division—Westward	2 and 3
First Sub-Division—Eastward	4 and 5
Second Sub-Division	6
Third Sub-Division	7
Fourth Sub-Division	7
Special Instructions	8, 9 and 10
Maximum Clearances	11

NORTHERN PACIFIC RAILWAY COMPANY

Duluth and Superior Terminals

TIME TABLE 203

In Effect at 12:01 A. M. Central or 90th Meridian Time.

Thursday, October 23, 1941

For the Government of Employes only. The Company reserves the right to vary therefrom at pleasure. Be positive that you have the Current Time Table and destroy all previous numbers. Read carefully the Special Instructions and always carry for reference a copy of TRANSPORTATION RULES.

W. W. JUDSON, General Manager.

P. H. McCAULEY, General Superintendent of Transportation.

G. H. JACOBUS, Superintendent.

		-5	W W .	<i>E</i> 8		1 1 1	FIRST	CLASS		9			n	Time Table No. 203
88.		<u>.</u>	65	57	303	405	51	201	61	401	407	55	R. Jet.	October 23, 1941
Turn Tables, Wyes and Yard Limits.	ity	Station Numbers	N. P. 65	N. P. 57	D. W. & P.	D M.&I.R.	N. P.	D M.&I.R.	N. P.	D.M &I.R. 12	D.M.&I.R.	N. P. 55		Superseding No. 202.
Tab Yard	Car Capacity of Sidings.	ion N	Passenger	Passenger	Passenger		Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Distance from East D. M. & I.	STATIONS
Tur	of Si	Stat	Daily	Daily	Ex. Sun.	Daily	Ex. Sun.	Daily	Ex. Sun.	Daily	Daily	Daily	Dist East	Telegraph Offices and Calls
X WC	13					ь 5.46 ры	180 30 1			l 8.25 an	L 8.00an		0.0	EAST D. M. & I. R. JCT
YXZ	Yard	WB 71	L 11.30 PM	L 9.00 PM		A 5.50 ₽M	L 2.20 PM	L 8.35 AM	L 8.30 AM	A 8.30 AM	a 8.05 am	ъ 7.50 ам	0.9	DUDULUTHDN
x	88		11.33	A 9.03 PM	DESCRIPTION OF THE PROPERTY OF		A 2.24 PM	8.38	8.33			а 7.53 ам	1.9	GARFIÊLD AVE
x		L 2	t 11.35		7.21			8.39	s 8.35				2.2	20TH AVE. WPD
x	e "e	L 02	11.37		7.22			A 8.41 AM	8.36				2.8	SOO LINE CROSSING
x	18												3.6	
x			11.40		А 7.29 ры				8.40				4.4	OLD W. & P. JCT
x	0.00	L 04	s 11.44						s 8.43				5.1	WUWEST DULUTHDN
X		L 5	A 11.50 ₽M						а 8.45 м				5.8	E WEST DULUTH JCT1
ŀ			-										7.0	D. T. CROSSING
8													8.1	RIVERSIDE
5, 8		LB 2											8.5	SPIRIT LAKE
5		LB 3					-						9.7	MORGAN PARK
		ŀ	(0)										10.7	BOAT CLUB
	E E	LB 5	****				3 3	-					12.4	NEW DULUTH
		LB 8											15.1	FOND DU LAC
			Daily	Daily	Ex. Sun.	Daily	Ex. Sun.	Daily	Ex. Sun.	Daily	Daily	Daily	a 6	2
			.20	.03	.10	.04	.04	.06	.15	.05	.05	.03		Time Over Sub-Division
			14.7	20.0	15.0	13.5	15.0	19.0	19.6	10.8	10.8	20.0		Average Speed Per Hour

o s	Workstroom and	7 :		FIRST	SUB-D	IVISIO	N	5541 ×	l =	WES	TWARI	3
Time Table No. 203	SECONE	CLASS				E 1 TELL		w v	1 .			7 X =
October 23, 1941	623	627		5 121		1 1 1/3						
Superseding No. 202.	N. P. 623	N. P. 627	f of gift	1 18 2 2 3	u E	- 1*	El ni e					
STATIONS	Freight	Freight	, A	63 8		7 - 2			-	6	3. 8	10 14k s
Telegraph Offices and Calls	Daily	Daily		die F		- 78	y s	e (a)			. 1	
20TH AVE. WPD 0.6 N. & I. R. JCT 0.8 0.8 0.8 0.8 0.8 0.8 0.8 0.8 0.8	L 6.00 рм A 6.03 рм	7.35 pm - 7.39 7.40 - 7.42 - 7.48										
WUWEST DULUTHDN 0.7WEST DULUTH JCTP 1.2D. T. CROSSING 1.1		7.51 A 7.55 PM										
	Daily	Daily					3					
Time Over Sub-Division Average Speed Per Hour	20.0	.20			9	179	-	<u> </u>	<u> </u>			

4	EA	ST	WARD				FI	RST S	UB-DI	VISION					3
	E E	iii	u :	ro ^{FR} e Ho		÷	FI	RST CL	ASS	*					Time Table No. 203
les,		,	10 %	56	402	404	204	62	52	400	304	58	66	-	October 23, 1941
Water, Fuel, Scales, Turn Tables, Wyes and Yard Limits.	oity	Митьегв.	, s s	N. P. 56	D.M.&I.R. 11	D.M.&I.R. 9	D.M.&I.R. 2	N. P. 62	N. P. 51	D.M.&I.R. 5	D. W. & P.	N. P. 58	N. P. 66	from Lac.	Superseding No. 202
ter, Fu ra Tab I Yard	Car Capacity of Sidings.	Station N		Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Distance Fond du	STATIONS
Tu	D o	Sto		Daily	Daily	Daily	Daily	Ex. Sun.	Ex. Sun.	Daily	Ex. Mon.	Daily	Daily	Fo	Telegraph Offices and Calls
wer			1 1 3		а 6.00ры	17.5				а 9.04 м	l .			15.1	0.9
WCT YXZ	Yard	WB 71		A 11.00 PM	L 5.55 PM	L 4.25 PM	A 4.15 PM	A 12.15 PM	A 11.45 AM	L 9.00 AM		A 8.00 AM	a 6.30 an	14.2	DUDUĻUTHDN
x		/A		I 10.55 PM			4.12	12.12	L 11.42 M		A 8.38 AM	L 7.57AM	6.25	13.2	0.3
x		L 2					4.11	12.11			8.35		f 6.22	12.9	20TH AVE. WPD
x		L02					L 4.08 PM	12.09			8.34		6.19	12.3	20TH ÄVE. WPD 0.0 0.8 0.8
$\overline{\mathbf{x}}$			100000											11.5	SOO LINE CROSSING.
x								12.05			L 8.28 AM		6.14	10.7	ED. W. & P. JCT }
x		L04						s 12.03					s 6.12	10.7 10.0 9.3	WUWEST DULUTHON
YX		L 5						L 12.01 PM					L 6.03 AM	9.3	WEST DULUTH JCT.P
												ļ		8.1	D. T. CROSSING
														7.0	RIVERSIDE
		LB2								- 1				6.6	
		LB3												5.4	MORGAN PARK
														4.4	BOAT CLUB
n i		LB5												2.7	NEW DULUTH .PD
		LB8												0.0	FOND DU LAC
				Daily	Daily	Daily	Daily	Ex. Sun.	Ex Sun.	Daily	Ex. Mon.	Daily	Daily		· *
				.05	.05	.05	.07	.14	.03	.04	.10	.03	.27		Time Over Sub-Division

20.0

13.5

15.0

20.0

10.9

21.0

16.3

12.0

10.8

10.8

Average Speed Per Hour

		1055 1000 1000 1000 1000 1000 1000 1000		FIRST	SUB-D	IVISIO	1	9 1 1		EAS	TWARI	5
Time Table No. 203	8, 95 0	3 , 5		81	5일 전 12 12 12 12 12 12 12 12 12 12 12 12 12	SECOND	CLASS					
October 23, 1941	624	626	628					1.25				A S.C.
Superseding No. 202	N. P. 624	C. M. St. P. & P. 626	N. P. 628		100 m	2 S 10		= 100			- XI	70 M
STATIONS	Freight	Freight	Freight	8 A		1 2	: 1	5.0		1 2 E	. E 701	F 18
Telegraph Offices and Calls	Daily	Daily	Daily		, A.	= =	: _x	Б -	. E	n =	76 T	
DOUBLE TRACK MEST D. M. & I. R. JCT DU		3.46 3.43 L 3.40 AM	4.30 AM 4.20 4.09 4.06 4.00 3.58 L 3.55 AM									
Time Over Sub-Division Average Speed Per Hour	Daily .20	Daily .20	Daily .35									

THE PROPERTY OF THE PROPERTY O

6	WESTV	VARD		n = 8 = n	E	SECO	ND SU	JB-DIV	ISION				e H e	
SEC	OND CL	ASS	1 10		is e f	2 6-c	FIRST	CLASS					TimeTableNo.203	81
629	625	623		35	57	89	93	19	51	23	55	65	October 23, 1941	
N. P. 630	C. M. St. P. & P. 625	N. P. 623		G. N. 35	N. P. 57	Omaha 510	Omaha 512	G. N. 19	N. P. 52	G. N. 23	N. P. 55	N. P. 65	Superseding No. 202	from Ave.
Freight	Freight	Freight	Ε	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	STATIONS	istance entral A
Sun., Tue. Thur., Fri.	Daily	Daily		Ex. Sun.	Daily	Daily	Daily	Daily	Ex. Sun.	Daily	Daily	Daily	Telegraph Offices and Calls	
		L 6.03 PM			L 9.03 ₽M				L 2.24 PM		L 7.53 AM		GARFIELD AVE	7.3
L 10.00PM	L 7.40 PM	6.04			9.05				2.26		7.55		RICES POINTP	6.5
10.05	7.45	6.06		L 9.36 PM	9.06	L 8.22 PM	L 5.05 PM	L 4.36 PM	2.28	L 8.06 M	7.57		BRIDGE SWITCH	6.0
10.09	7.49	6.09		9.39	9.09	8.25	5.08	4.40	2.31	8.10	8.00		ELEVATOR STATION	5.1
10.11	7.51	6.11		9.42	9.11	A 8.28 PM	A 5.10 PM	4.42	2.33	8.12	8.02		OMAHA CONN	4.4
				s 9.45	s 9.12			s 4.45	s 2.34	s 8.15	s 8.05	L-12.06 AM	BYSUPERIOR U.D.,PDN	4.1
10.20	8.25	6.22	1	9.46	9.14			4.46	2.35	8.16	8.06	12.08	호달성 SBELKNAP STP	3.7
A 10.45 PM	A 8.40 PM	а 6.50ры		A 9.55 PM	As 9.25 PM			а 4.53 ры	As 2.45 PM	А 8.23 АМ	As 8.14 AM	As 2.20 AM	AJ. CENTRAL AVEDN	0.0
Sun., Tue., Thur., Fri	Daily	Daily		Ex. Sun.	Daily	Daily	Daily	Daily	Ex. Sun.	Daily	Daily	Daily	= 1	
.45	.60	.47		.19	.22	.06	.05	.17	.21	.17	.21	.14	Time Over Sub-Division	
8.7	6.5	9.3		19.0	19.9	13.7	19.1	21.1	20.8	21.1	20.8	17.1	Average Speed Per Hour	

EASTWARD TRAINS ARE SUPERIOR TO TRAINS OF THE SAME CLASS IN THE OPPOSITE DIRECTION.

DOUBLE TRACK BETWEEN GARFIELD AVENUE AND OMAHA CONNECTION, EXCEPT OVER MINNESOTA DRAW ON ST. LOUIS RIVER BRIDGE. DOUBLE TRACK BETWEEN BELKNAP STREET AND CENTRAL AVENUE.

FIRST CLASS TRAINS USE L. S. T. & T. RAILWAY BETWEEN OMAHA CONNECTION AND BELKNAP STREET

AND BE GOVERNED BY L. S. T. & T. TIME TABLE, RULES AND REGULATIONS.

ATT A A STY	arra :	TE A PATTY A	
CHULLINI	SIIR_	DIVISION	
	171111		

EASTWARD

	g o se			Time Table No. 203		19 19 19	i santana		FIRST	CLASS	n *	0	ton and		SECOND CLASS
Water, Fuel, Sonles, Turn Tables, Wyes and Yard Limits.		ra.	L	October 23, 1941	66	36	94	58	52	96	24	20	56	N 3557	630
uel, Soles, W	oity.	Numbers.	from Ave.	Superseding No. 202	N. P. 66	G. N. 36	Omaha 511	N. P. 58	N. P. 51	Omaha 513	G. N. 24	G. N. 20	N. P. 56	p	N. P. 629
ter, F rn Tak Yard	Car Capacity of Sidings.	Station N	Distance Garfield /	STATIONS	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger	Passenger		Freight
Tul Bud	20	Ste	E G	Telegraph Offices and Calls	Daily	Ex. Mon.	Daily	Daily	Ex. Sun.	Daily	Daily	Daily	Daily		Mon., Wed. Fri., Sat.
X WCT YXZ	Yard	L 1	0.0 0.8 1.3	GARFIELD AVEP 0.8RICES POINTP 0.5BRIDGE SWITCH		A 6.53 AM	A 7.18AM	A 7.57 AN 7.54 7.52	A 11.42AN 11.38 11.36	A 11.46 AM	A 11.52AM	A 7.54PM	A 10.55 PM 10.53 10.52		A 8.30 AM 8.27
x x			2.2	ELEVATOR STATION 07 OMAHA CONN			7.14 L 7.12A	7.49 7.46	100000000000000000000000000000000000000	11.43 L11.40 AM	7 400 0000	7.49 7.46	10.48		8.23 8.20
X X WYX	Yard	WB 67	3.6	BYSUPERIOR U. DPDN 0.4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	5.38	6.41		s 7.44 7.41 L 7.33 AM	s 1.29 1.27 L		s .43 .40 L	в 7.45 7.41 L 7.36рм	s 10.44 10.40 L 10.35 PM		1.8.00 AM
			110		Daily	Ex. Mon.	Daily	Daily	Ex. Sun.	Daily	Daily	Daily	Daily		Mon. Wed. Fri., Sat.
		-		Time Over Sub-Division Average Speed Per Hour	22.3	.20 18.0	13.7	18.2	19.0	13.7	18.9	20.0	21.9		13.0

EASTWARD TRAINS ARE SUPERIOR TO TRAINS OF THE SAME CLASS IN THE OPPOSITE DIRECTION.

DOUBLE TRACK BETWEEN GARFIELD AVENUE AND OMAHA CONNECTION, EXCEPT OVER MINNESOTA DRAW ON ST. LOUIS
RIVER BRIDGE. DOUBLE TRACK BETWEEN BELKNAP STREET AND CENTRAL AVENUE.

FIRST CLASS TRAINS USE L. S. T. & T. RAILWAY BETWEEN OMAHA CONNECTION AND BELKNAP STREET
AND BE GOVERNED BY L. S. T. & T. TIME TABLE, RULES AND REGULATIONS. SPECIAL INSTRUCTIONS PAGES 8, 9 AND 10.

W	EST	`WA	RD	22 22 22 22			TH	IRI	SUB-DIVISION	11 31			EAST	WARD	7
				FIF	RST CLA	ss	5		Time Table No. 203		R 7	FII	RST CLA	SS	
Sales, Tyes		ż	65	53	317	313	311	it.	October 23, 1941	i R	54	66	318	312	314
Water, Fuel, Scales, Turn Tables, Wyes	acity 8.	Numbers.	N. P.	D.S.S. & A.	Soo Line	Soo Line	Soo Line	nee from Duluth Jet.	Superseding No. 202	from U. D.	D.S.S.&A.	N. P.	Soo Lane	Soo Line	Soo Line
ter, Fr. Ta	Car Capacity of Sidings.	Station 1	Passenger	Passonger	Passenger	Passenger	Passenger	of	STATIONS	Distance Superior	Passenger	Passenger	Passenger	Passenger	Passenger
₽ T. a	S S	Sta	Daily	Ex. Sat.	Daily	Daily	Ex. Sun.	Dista	Telegraph Offices and Calis	Dis 8ug	Ex. Sun.	Daily	Daily	Ex. Sun.	Daily
YX X		L5	ь II.50ры II.53		- 100	2 E E		0.0	WEST DULUTH JCTP			A 6.03 M			
x				L 8.13 PM	L 5.43 PM	L 1.13pm	L 7.33 AM	0.8	DW&P. BERWIND JCT P)	3.0 2.3	А 5.16м	6.01 5.58	A 7.43 AM	A 4.02 PM	A 5.51 PI
x		8	12.05 AF	A 8.18 PM	A 5.48 PM	A 1.18m	A 7.38 AM	1.8	GRASSY POINT CARAGE STATE OF THE POINT CARAG	1.8	L 5.11AM	5,49	т. 7.38м	L 3.57pm	L 5.46m
<u>x</u>		WB 67	A = 1 2.06 AM		X 3.4012	1.107	7.50	3,6	SUPERIOR U. DPDN		D 3.11 A	L 5.40 AM		1. 3.31 FR	L 3.40A
			Daily	Ex. Sat.	Daily	Daily	Ex. Sun.				Ex. Sun.	Daily	Daily	Ex. Sun.	Daily
			.16	.05	.05	.05	.05	tecrescon ex	Time Over Sub-Division		.05	.23	.05	.05	.05
			13.5	24.0	24.0	24.0	24.0		Average Speed Per Hour		24.0	9.4	24.0	24.0	24.0

EASTWARD TRAINS ARE SUPERIOR TO TRAINS OF THE SAME CLASS IN THE OPPOSITE DIRECTION.

U. a			SEC	OND CL	ASS	FIRST	CLASS	- 1	Time Table No. 203		FIRST	CLASS	SEC	OND CL	ASS
yes		÷	7697v	629	631	51	53		October 23, 1941		52	54	632	630	
les, W	oity	umber		i wasans iA "	D.S.S.&A.	: = # # #	D.S.S.&A.	율.	Superseding No. 202	from	m ye .	D.S.S. & A. 8	D.S.S. & A. 22	The state of the s	
r, Fr Tab Yard	Capa	tion Nu		Freight	Freight	Passenger	Passenger	End	STATIONS	stance ntral A	Passenger	Passenger	Freight	Freight	
Water, Fuel, Scales, Turn Tables, Wyes and Yard Limits.	Car Capacity of Sidings.	Stati	8 no	Mon. Wed. Fri., Sat.	Daily	Ex. Sun.	Ex. Sun.	Dista East	. Telegraph Offices and Calls	Dista	Ex. Sun.	Ex. Sat.	Daily	Sun., Tue., Thur., Fri.	- 3
WY X X	Yard	63		L 7.45 AM	L 5.20 AM	L . OAM	L 4.51 AL	0,0	P)	4.0	As 2.55PM	a 8.55 pm	A 12.15AM	A 10.55 PM	
â	Yard	65		7.46	A 5.21 AM	11.11	A 4.52 AM	- 54	C. St. P. M. & O. Crossing		2.54	L 8.54 PM	L 12.14AM	10.54	
		nēs.	_a_8	7.49		11.14		1.8	HILL AVEP	2.2	2.51			10.51	
x								2.9	SOO LINE CROSSING.	1.1		*			
WYX	Yard	67	and westernoons of the	A 7.55 AM		Asl 1.19 M		4.0	AJCENTRAL AVEDN	0.0	L 2.45 PM	201 14 (201) (201		L 10.45 PM	
	N 1		fine a co	Mon-Wed- Fri., Sat.	Daily	Ex. Sun.	Ex. Sun.				Ex. Sun.	Ex. Sat.	Daily	Sun., Tue., Thur., Fri.	in a
SHOWER THE				.10	.01	.09	.01		Time Over Sub-Division		.10	.01	.01	.10	
		5	8	24.0	12.0	26.7	12.0		Average Speed Per Hour		24.0	12.0	12.0	24.0	A Res 13

EASTWARD TRAINS ARE SUPERIOR TO TRAINS OF THE SAME CLASS IN THE OPPOSITE DIRECTION.

SPECIAL INSTRUCTIONS PAGES 8, 9 AND 10.

SPECIAL INSTRUCTIONS

FIRST SUBDIVISION

- 1. At Fifth Avenue West-Main track switch will be kept set for Union Depot.
- 2. At Garfield Avenue-Junction switches will be kept set for First Sub-Division.

Trains stop not less than two hundred (200) feet from Junction Switch and crossover used by D. W. & P. and not proceed until track is known to be clear.

- 3. At Nineteenth Avenue West-Trains using the Dick tracks must not block crossing.
- 4. At Twenty-first Avenue West-Telephone at crossover-Eastward trains call yard (3 rings) for route when necessary.
- 5. At West D. M. & I. R. Jct. Interlocking-Trains will call for route as follows:

Martins track to D. M. & I. R. yard. D. M. & I. R. yard to Martins track. 000

000 Martins track to Westward main. 000-

0000 Martins track to D. T. Main.

D. T. main to Martins track. 0000

Westward main to D. M. & I. R. yard. **—** 0

— o D. M. & I. R. yard to Eastward main. Through Main Line Movements.

6. At West Duluth Jct.—Switch at west end wye will be kept set and locked for first sub-division.

Switch engines will use west leg of wye and Fond du Lac line but will not leave cars on these tracks.

Switch at end of double track is dual control. Normal position is for the westward track. If signals fail to clear switch must be examined, and if not in proper position first throw power lever, then operate switch with hand-throw lever. Power lever must not be returned to normal position until after final move over switch is made. Both levers must be left in normal position and locked. Trains setting out on Fond du Lac and other tracks must be sure switches are lined for such movement.

- At Fond Du Lac—Trains will call upper Power Plant (Douglas 50) from New Duluth and secure permission to use track between Fond du Lac and Power Plant, but must secure authority from Chief Dispatcher to use track to lower Power Plant.
- 8. Yard Limits-Between D. M. & I. R. connection at Fifth Ave. East and Lake Superior Division yard limit sign West of West Duluth Jct.
- 9. Derail Switches-Fond du Lac.
- Bridge and Engine Restrictions—Between West Duluth Jct. and Fond du Lac—engines heavier than Class T not permitted. Between Fond du Lac and upper Power Plant-engines heavier than Class L-9 not permitted, and engines must be headed East. Bridge 4, five (5) MPH.
- 11. Speed Restrictions—Over Sub-division, fifteen (15) MPH. Between Fond du Lac and upper Power Plant, eight (8) MPH.
- 12. Register Stations-Duluth Union Depot for trains arriving at or departing from Fifth Ave. Yard or Union Depot, Rices Point Yard office for other trains. West Duluth.
- Register Exceptions—At West Duluth trains register by Form 608.
 A check of register on Form 602 may be issued by operator when authorized by train dispatcher, either instead of, or in addition to. train order check.
- 14. Clearance Exceptions—Trains originating at East D. M. & I. R. Jct., Garfield Ave., 20th Ave. West, West D. M. & I. R Jct., D. W. & P. Jct., West Duluth Jct. and Fond du Lac will not require clearance. At West Duluth, Eastward trains will not require clearance if train order signal is in proceed position.

SECOND SUBDIVISION

1. At Garfield Avenue-Junction switches will be kept set for First Sub-Division.

Trains will stop not less than two hundred (200) feet from Junction switch and crossover used by D. W. & P. and not proceed until track is known to be clear.

2. At Rices Point-Spring switches, roundhouse lead, 900 feet South of coal dock, indicate-

> Yellow-Straight Track. Green-Roundhouse Lead.

3. Between Bridge Switch and Elevator Station, St. Louis River Bridge-Interlocking signals govern use of tracks.

Single track over Minnesota Draw.

The three-arm semaphore on eastward track west of Minnesota Draw indicates position of double track switch, position of draw and route:

Top Arm-Northern Pacific Middle Arm—Great Northern Bottom Arm—C. St. P. M. & O.

The two-arm semaphore on westward track east of Elevator Station indicates route:

> Top Arm—Straight main track Bottom Arm-Great Northern Freight Track

All trains will stop before entering onto Wisconsin draw.

All eastward trains will stop before entering onto Minnesota draw. Westward trains entering onto Minnesota draw will be governed by signal at the approach and, if proceed signal is received, will not be required to stop.

- 4. At Superior-Trains using tracks of L. S. T. & T. Railway between Omaha connection and Belknap Street will be governed by L. S. T. & T. time table, rules and regulations.
- 5. At Central Avenue-Westward trains and engines may use eastward main track between west lead from yard and Junction with Fourth (Terminal) Sub-Division without protection. All trains will pass through this territory at restricted speed, on both tracks.
- 6. Yard Limits-From Garfield Ave. to yard limit sign West of 28th Street, Superior, and from yard limit sign East of Central Ave. to the yard limit sign just East of Soo Line crossing on Terminal Fourth Sub-division, and yard limit sign West of Central Ave. on Second Sub-division of Lake Superior Division.
- 7. Derail Switches-At approach to Minnesota Draw from Duluth. At Elevator Station. At Superior—just East of N. P. freight house.
- 8. Speed Restrictions—At Bridge 2.1, St. Louis River—Twenty (20) MPH over draw spans. At Superior-Fifteen (15) MPH over switches at Belknap Street and Omaha connection, and restricted speed on L. S. T. & T. tracks between these stations. At Central Avenue—Twenty (20) MPH over highway crossings.
- 9. Register Stations: Rices Point for second class and inferior trains, except passenger Superior Union Depot for trains routed via L. S. T. & T. Ry. Central Avenue.
- 10. Register Exceptions—At Central Avenue trains register by form 608. A check of register on Form 602 may be issued by operator when authorized by train dispatcher, either instead of, or in addition to. train order check.
- 11. Clearance Exceptions: Trains originating at Garfield Ave., Rices Point (Yard), Bridge Switch, Elevator Station, Omaha Conn. and Belknap St. will not require clearance. At Central Ave. eastward trains will not require clearance if train order signal is in the proceed position.

THIRD SUBDIVISION

1. At West Duluth Jct.:

Switches on east leg of wye will be kept set for Third (Terminal) Sub-Division main track.

 Speed Restrictions—Bridge 94.6, Grassy Point, twenty (20) MPH over draw span.

At West Duluth Jct., trains and engines run at restricted speed around east leg of wye and passing Zenith Furnace Plant, looking out for yard engines working on main track.

 Register Station—Superior Union Depot for trains routed via L. S. T. & T. Ry.

4. Clearance Exceptions:

Trains originating at West Duluth Jct., Berwind Jct. and L. S. T. & T. Ry. Jct. will not require clearance.

A check of register on Form 602 may be issued by operator when authorized by train dispatcher, either instead of, or in addition to, train order check.

5. Trains using tracks of L. S. T. & T. Ry. from L. S. T. & T. Ry. Jct. be governed by L. S. T. & T. Time Table, Rules and Regulations.

FOURTH SUBDIVISION

 At East End—Normal position of switch at end of double track is for westward trains.

The approach signal of interlocking is an automatic block signal governing single track to end of double track and westward track to Newton Ave. interlocking. Eastward D. S. S. & A. and C. St. P. M. & O. trains and engines will use westward main track between Newton Ave. interlocking and end of double track as single track, under single track and yard limit rules.

At Central Ave.—Normal position of switch at end of double track on east leg of wye is for eastward trains.

Normal position of switch at Junction of Fourth and Second (Terminal) Sub-Divisions is for Second Sub-Division.

East leg of wye is single track and sharp curvature, all trains will run at restricted speed.

3. Yard Limits—Tracks between yard limit signs West of East End and East of Allouez.

At Allouez, track No. 2 must not be used by ore trains.

 Speed Restrictions—Engines Classes W or heavier, fifteen (15) MPH over trestle approach to Ore Dock.

5. Register Stations:

Central Ave. Soo Line 21st St. Yard Office, Superior, for D. S. S. & A. Ry.

- Register Exceptions—At Central Ave. trains register by form 608.
 A check of register on Form 602 may be issued by operator when authorized by train dispatcher, either instead of, or in addition to, train order check.
- Clearance Exceptions—Trains originating at East End and Hill Ave. will not require clearance.

ALL SUBDIVISIONS

- Transportation Rule 11 is modified as follows: A train finding a fusee burning on or near its track may proceed at restricted speed without stopping.
- Lights will be displayed at night on all main line train order signals.
 On Branch line sub-divisions where lights are not displayed on day-office train order signals, all trains will positively ascertain position of signal and be governed by the day indication.
- 3. Transportation Rule D-97 applies to all divisions.

- 4. Transportation Rule 105 is modified as follows: When a siding of an assigned direction is blocked with cars, or taken out of service for any reason, the siding of the opposite direction will be used as a single siding. At lap sidings, unless otherwise provided, trains taking siding must head in at the lap.
- 5. IN AUTOMATIC BLOCK SIGNAL TERRITORY—When moving with the current of traffic, or on single track, where the automatic block signals governing the track in use are of the semaphore type and can be plainly seen from the rear of a standing train to be at stop, such signal being not less than one-half mile from the rear of such train, it will not be necessary to protect the train by a flagman. Under all other circumstances Rule 99 must be observed.

Transportation Rule 501B, is modified as follows: INDICATION—Approach next signal prepared to stop. Block is clear; second block in advance is not clear.

Transportation Rule 509B, is modified as follows: It must be understood that such signal indication may be due to an opposing train proceeding into the same block at the opposite end under an approach signal indication Rule 501B and before proceeding into the block every precaution consistent with running orders and the nature of the track ahead should be taken to insure safe movement through the block.

When a train dispatcher desires to advance a train from a station where by the rule it should enter the siding before passing a train order office, he may instruct the operator to use white signal as prescribed by Transportation Rule 12-c. The engineman may then continue to move his train on the main track to the signal at restricted speed and there be governed by train orders that are addressed to his train.

- Transportation Rule 606:—Emergency Signals are not used at interlockings or drawbridges operated by the Northern Pacific Railway.
- 7. Transportation Rule 728 is modified as follows: The red flag by day, and in addition the red light at night, will be placed twenty (20) rail lengths distant from the point of obstruction instead of fifty (50) rail lengths. The flagman will be located with the yellow signals, one mile distant beyond the red signals. On the approach of a train the flagman will display the yellow signals, which must be acknowledged by the enginemen in accordance with Rule 14 (g).
- 8. Transportation Rule 1062, requiring the making of running brake test on passenger trains, must also be observed on all passenger trains following departure from terminals, or from a station at which either train or engine crews, or both of them, have been changed, or where switching has been done.
 Enginemen will acknowledge proceed signals of trainmen by two (2) short blasts of the whistle.
- 9. When a siding is to be used temporarily as a main track, the switches will be set and locked for the siding and must be protected by flagman until train order covering the movement is issued to all trains and the section foreman of that section notified; the flagman to remain until released by the train dispatcher.
- Helper engines waiting to help trains will keep clear of main track until train to be helped has arrived and stopped.
- 11. In case of failure of communicating signal system on passenger trains, and on freight trains when conditions permit, enginemen will receive "proceed" signal before passing any station.
- 12. SPEED RESTRICTIONS—Except as otherwise provided:
 Passenger trains, sixty (60) MPH. Freight trains, fifty (50) MPH,
 except when restricted to lower rate of speed by engine speed restrictions.

ENGINES—All A, Q and P Classes, and Classes S-4 and T, sixty (60) MPH, except when used on passenger trains where higher speed is authorized; Z-6, sixty (60) MPH, other Z Classes, thirty-five (35) MPH. All other Classes, fifty (50) MPH. Switch engines under steam, moving between stations, fifteen (15) MPH.

ALL TRAINS AND ENGINES—Fifteen (15) MPH through crossovers, turnouts and gauntlets; twenty-five (25) MPH passing telegraph offices where orders are delivered; thirty (30) MPH over interlocked crossings, and when handling steam wrecking derrick, pile driver or locomotive crane.

To avoid damage to rail and bridges by moving locomotives having main or side rods down, over the road at too high a speed, the following speeds will be maximum permitted:

ON MAIN LINE-

With main and side rods removed: All A and Q Classes All other Classes 25 MPH With main rods removed and side rods in place: **35 MPH**

All A and Q Classes All other Classes

ON BRANCH LINES-With either or both main and side rods removed:

All A and Q Classes

25 MPH All other Classes 20 MPH OVER BRIDGES-Main or Branch Line 20 MPH

Engines with either or both main and side rods removed shall not be moved over any bridge at a speed in excess of twenty (20) MPH and the speed shall be further reduced over bridges which carry speed restrictions against the class of power being so moved. In the latter case, the speed of an engine with rods removed shall be reduced over the bridge to one-half the restricted speed for that engine in working order, as shown under "Bridge and Engine Restrictions."

Dead engines with all rods up or in place, the piston rod being parted from the crosshead and removed and the valve motion disconnected and blocked, may be moved in trains at not to exceed the permissible speed of freight trains operating in the territory over which such engines are moved. Bridge or other restrictions applicable to these engines when in operating condition to be observed. For engines coming from the shop, to prevent running hot, authorized

maximum speed is: All A and Q Classes

All other Classes

30 MPH

30 MPH

 Bridge Restrictions for Single and Double Header Engines— Where no mention is made of single or double heading, the instructions apply alike to single and double header engines of each class.

An engine of any class double-headed with an engine of lighter class will carry the same restrictions as if the heavier engine were doubleheaded with its own class, unless instructions to the contrary have been issued.

14. Spring Switches:

Maximum speed for all facing point and trailing point movements through switch fifteen (15) MPH. Trailing movements on the track for which the switch is normally lined may be made at normal speed. Trains trailing through or stopping on a spring switch must not back up or take slack until points have been thrown by hand. Flying switches over or through spring switches are prohibited. When operated by hand, lever must be moved slowly, keeping a steady pressure on the handle until the switch is thrown and the handle is in the notch on the switch stand provided for it. When signal governing block in which spring switch is located is at stop, or where automatic block signals do not govern account trains running against current of traffic, facing point movements must not be made over switch until points have been examined. Sand must not be used over points of spring switches.

- 15. Before moving a work or wrecking train, the whistle signal (14-b) or (14-h) must be sounded for the protection of men working about such trains.
- 16. Gas-Electric motor cars handled in freight trains, must be behind

Test of hand brakes of Gas-Electric motor cars must be made once each trip. If crew has charge of moving car prior to leaving initial station, test will be made during such movement; otherwise, as soon as possible after leaving initial station. On cars equipped with "Deadman's Control", conductor and engineman will cooperate in making test.

- 17. Precautions must be taken on double track to prevent accidents from swinging doors or other loose construction attached to cars or locomotives. Trains handling logs must stop when being met or passed by passenger trains.
- 18. First class trains must move within yard limits at restricted speed.

- 19. Second class and inferior trains and engines may run ahead of delayed first class trains.
- 20. Extra trains, work extras and switch engines do not require train orders for movement between West Duluth Jct. and Duluth, between Central Ave. and Rice's Point, between Central Ave. and East End, and between West Duluth Jct. and Superior.
- 21. Flagman must be stationed on the rear car, at all times, and be provided with proper flagging equipment. In case train is stopped on main track, flagman must go back immediately with stop signals a sufficient distance to insure full protection to his train. Conductors and switch foremen will be held responsible for the strict observance of this rule.
- 22. The D. T. main track is the northmost track between the Hanna Coal Dock crossing and connection with Grassy Point main track. All switches leading from this track, when not in use, will be left lined for D. T. Ry.
- 23. All trains and engines using D. T. main track from connection of Missabe coal dock to east end of Zenith Furnace Company's lead, on Grassy Point line, will move in both directions at restricted speed, expecting to find the D. T. main track occupied.
- 24. D. T. connection, located at east end of Zenith Furnace Company's lead, Grassy Point line, will be considered a railroad crossing. Trains and engines using this connection will come to full stop and make sure that track is clear before proceeding.
- 25. BULLETIN STATIONS—

Duluth-Rice's Point vard office. Rice's Point roundhouse. Union Depot.

26. STANDARD TIME CLOCKS—

Duluth, Union Depot. Rice's Point Roundhouse and Yard Office.

27. WATCH INSPECTORS-

Duluth, O. M. Hopper—Med. Arts Bldg. Duluth, Harlan Wells, 8 No. 5th Ave. West. Duluth, H. W. Schmidt, 10 No. 21st Ave. West. West Duluth, W. F. Hurst, 301 No. Central Ave. Superior, L. G. Howatt, 1425 Tower Ave.

NOTE

Schedule meetings or passing stations are indicated in full-faced type; numbers of the trains meeting, passing or being passed will not be shown.

RAILROAD CROSSINGS AND INTERLOCKINGS.

First Sub-division

West D. M. & I. R. Jct., Interlocking. Soo Line Crossing, Interlocking. D. W. & P. Jct., Interlocking. West Duluth Jct., Automatic Interlocking. West Duluth Jct., D. T. Ry. Crossing. Morgan Park, Minnesota Steel Co. Crossing.

Second Sub-division

Bridge Switch and Elevator Station, Interlocking. St. Louis River Drawbridge. Minnesota Draw, Interlocking. Wisconsin Draw, Interlocking. Superior, Winter St., L. S. T. & T. Ry. Crossing.

Third Sub-division

D. T. Connection. Berwind Jct., Interlocking, is also junction with Soo Line and D. W. & P. Grassy Point Drawbridge, Interlocking. G. N. Ry. Crossing. L. S. T. & T. Ry. Crossing.

Fourth Sub-division

Newton Avenue. C. St. P. M. & O. Crossing, Interlocking. Soo Line Crossing, Interlocking.

1 2		×		LIMIT	OF LOA	D MEAS	UREME	NT	2 V	r Paraga	re Ni ex
3 s - 19 s - 2 s - 19 s - 2 s - 19 s				HEIG	HT ABO	VE TOP	OF RAI	L			
	1 ft. Wide	2 ft. Wide	3 ft. Wide	4 ft. Wide	5 ft. Wide	6 ft. Wide	7 ft. Wide	7 ft. 6 in. Wide	8 ft. Wide	Max. Height	Max. Width
1st Sub-division, Duluth to Fond du Lac	19' 0"	19' 0"	19' 0"	19' 0"	19' 0"	19' 0"	19' 0"	19' 0"	19' 0"	19' 0"	11' 6"
2nd Sub-division, Garfield Ave. to Central Ave.	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	11' 6"
3rd Sub-division, W. Duluth Jct. to Superior U. D.	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	11' 6"
4th Sub-division, East End to Central Ave	21′ 0″	21' 0"	21′ 0″	21′ 0″	21' 0"	21′ 0″	21′ 0″	21′ 0″	21′ 0″	21′ 0″	11' 6"

			LIMIT	OF LOA	D MEAS	UREMEN	T		3	
			HEIGI	IT ABO	VE TOP	OF RAIL				A.C.
	8 ft. 6 in. Wide	9 ft. Wide	9 ft. 6 in. Wide	10 ft. Wide	10 ft. 2 in. Wide	10ft.6in. Wide	11 ft. Wide	11ft.6in. Wide	Max. Height	Max. Width
1st Sub-division, Duluth to Fond du Lac	 19' 0"	19' 0"	19' 0"	19' 0"	19' 0"	19' 0"	19' 0"	19' 0"	19′ 0″	11' 6"
2nd Sub-division, Garfield Ave. to Central Ave.	 20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	11' 6"
3rd Sub-division, W. Duluth Jct. to Superior U. D.	 20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	20′ 3″	11' 6"
4th Sub-division, East End to Central Ave	 21′ 0″	21′ 0″	21' 0"	21′ 0″	21' 0"	21' 0"	21' 0"	21′ 0″	21' 0"	11' 6"

SPEED TABLE.

101 101 101	Time per Mile Min. Sec.		Miles per Hour	Time per Mile Min. Sec.		Miles per Hour	Time per Mile Min. Sec.		Miles per Hour	
	1 1 1 1 1	1 2 3 4	60 59 58 57.1 56.2	1 1 1 1	20 25 30 40 45	45 42.3 40 36 34.3	2 3 3 3 3	50 9 20 31	21.2 20 19 18 17	
	1 1 1 1	5 6 7 8	55.3 54.5 53.7 52.9 52.1	1 2 2 2 2	50 10 15 20	32.7 30 27.6 26.6 25.7	3 4 5 6	45 30	16 15 12 10 8	
	1 1 1	10 12 15	51.4 50 48	2 2 2 2	30 40 45	24 22.5 21.8	10			

C. W. COIL, Asst. Supt. H. J. COUNCILMAN, Trainmaster. E. J. WIGG, Chief Dispatcher.