

NORTHERN PACIFIC RAILWAY COMPANY

FARGO DIVISION

Special Instructions No. 8

**In Effect at 12:01 A. M.
Central Standard Time**

except

**Twelfth, Thirteenth and Fourteenth Subdivisions,
Mountain Standard Time.**

Wednesday, December 3, 1947

**These Instructions constitute a part of the Time
Table currently in effect.**

**Employees whose duties are in any way affected by
the Time Table must have a copy of The Current
Special Instructions and Current Time Table with
them on duty.**

**D. A. THOMSON,
Superintendent.**

**C. V. BERGLUND,
General Manager.**

**R. E. MATTSON,
General Superintendent of
Transportation.**

SPECIAL INSTRUCTIONS

ALL SUBDIVISIONS.

1. Speed Restrictions—	Maximum Speeds Permitted
Passenger trains.....	75 MPH.
Freight and mixed trains.....	50 MPH.
"J" Manifest freight trains.....	35 MPH.

The above speeds are subject to the restrictions of maximum speeds in miles per hour as shown by zones under each subdivision.

Reduce speed limits, within the zones listed, are designated by Advance-warning signs (diagonally upwards), Reduce speed signs (square with clipped corners) and Resume speed signs (vertical).

The Advance-warning signs are, except as otherwise specified, located approximately 3000 feet in advance of the Reduce speed signs, and the numerals on both signs indicate in miles per hour the maximum speed permitted from the Reduce speed sign to another Reduce speed limit, or to a sign indicating a higher speed, or to a Resume speed sign (RS).

If speeds authorized by zones or by Reduce speed signs, are greater than that prescribed below for certain trains or engines, such trains or engines must not exceed the prescribed speeds.

Locations where reduced speeds are required but not indicated by signs, are listed under the zones of maximum speeds permitted for each subdivision.

All trains and engines, except as otherwise specified:

Through crossovers, turnouts and gantlets, except where fixed signals provide otherwise.....	15 MPH.
Handling steam wrecking cranes, pile drivers, locomotive cranes and similar equipment.....	30 MPH.
Handling 4-wheel scale test cars—Main Line.....	35 MPH.
Branch Lines.....	25 MPH.

Picking up train orders from operators.....30 MPH.

Engines—	Handling trains	Running light
Classes—		
All A and Q (except on passenger trains where higher speed is authorized).....	60 MPH.	60 MPH.

Z-6, Z-7 and Z-8.....	60 MPH.	50 MPH.
Z-5, Y, Y-1, Y-3.....	40 MPH.	35 MPH.
Z-3, Z-4.....	35 MPH.	30 MPH.
S-4, T, T-1, W to W-5 inc., Y-2.....	50 MPH.	45 MPH.

Steam switch engines, without engine trucks, under all conditions.....15 MPH. 15 MPH.

660 HP diesel-electric switch engines, Nos. 125 to 131 inc.....45 MPH. 45 MPH.

5400 HP and 6000 HP diesel-electric road engines, 6000 series.....65 MPH. 65 MPH.

4500 HP diesel-electric passenger engines, 6500 series.....75 MPH. 65 MPH.

900 HP and 1000 HP diesel-electric switch engines and combination road-switch engines.....60 MPH. 60 MPH.

Coming from shops, under steam, to prevent running hot:

All A and Q and classes Z-6, Z-7 and Z-8.....	50 MPH.
S-4, T, T-1, W to W-5 inc., Y-2, Z-5.....	35 MPH.
Y, Y-1, Y-3.....	30 MPH.
Z-3, Z-4.....	25 MPH.

Main Line—With main and side rods removed:

All A and Q and classes Z-6, Z-7 and Z-8.....	30 MPH.
Z-5, S-4, T, T-1, W to W-5 inc., Y to Y-3 inc.....	25 MPH.
Z-3, Z-4.....	20 MPH.

With main rods removed and side rods in place:

All A and Q and classes Z-6, Z-7 and Z-8.....	35 MPH.
Z-5, S-4, T, T-1, W to W-5 inc., Y to Y-3 inc.....	30 MPH.
Z-3, Z-4.....	25 MPH.

Branch Lines—With either or both main and side rods removed:

All A and Q classes.....	25 MPH.
All other classes.....	20 MPH.

On bridges—With either or both main and side rods removed:

Steam switch engines, without engine trucks.....	15 MPH.
Other engines.....	20 MPH.

In the event the above speeds are in excess of 50% of the permissible speed for operating the engine in working order

over any bridge carrying speed restrictions, speed on such bridges shall be 50% of the permissible speed for engine in working order.

Dead engines going to shops or being transferred from one district to another with all rods up or in place, the piston rod parted from the crosshead and removed and the valve motion disconnected and blocked, may be moved in trains at not to exceed the permissible speed of freight trains operating in the territory over which the engines are to be moved, or the operating speed restriction for track or bridges for that class of engine, whichever is the lower.

Engines handled in this manner when coming from shops must not exceed the operating speeds specified for engines coming from shops under steam.

Diesel-electric, 660 HP Nos. 125 to 131 inc., when handled dead in train.....45 MPH.

Diesel-electric, other engines, when handled dead in train.....50 MPH.

Bridge or other restrictions must be observed for these engines the same as when in operating condition.

2. Single and Double Headers; operation—track and bridges—general.

Except as otherwise provided, double header operation of engines of the same class carry the restrictions applicable to single headers of that class. Double headers of engines of different classes carry the restrictions applicable to double headers of the heavier class of the combination.

Diesel engines—Except as otherwise provided, diesel-electric engines of the 6000 and 6500 series and all diesel switch engines may be operated over bridges under the same restrictions shown for Class T engines.

Wrecking cranes—250 tons, 45 to 48 inc. must not be coupled directly to engine or tender of engines Classes A-2 to A-5 inc. or Z-5 to Z-8 inc., but must be separated from them by at least two cars of not over 169,000 pounds total weight, for movement over bridges.

3. Use of Mars headlight on engines so equipped—

The Mars headlight may display either a white or red, stationary or oscillating light, to be used in addition to the standard headlight.

The Mars white light may be used in a stationary position as a substitute headlight in case of failure of the standard headlight, but will normally be used as an oscillating light during the time full display of standard headlight is required. The Mars oscillating red light will be used when head end protection is required, either by day or by night by engineer control, if the train becomes disabled or is stopped suddenly due to unusual occurrence with the possibility of an adjacent track being obstructed, or if it overruns the clearance point at a meeting or waiting point, or at the end of double track or at a junction, or in any other emergency situation.

The engineer of an approaching train, finding oscillating red light displayed, must stop and then be governed by conditions existing. If on an adjacent track which he finds unobstructed and safe for operation, he may proceed at restricted speed until the standing train displaying the oscillating red light has been passed. The Mars red light will be displayed in stationary position when a train is occupying the main track at a meeting point with an opposing train until the headlight of the opposing train has been dimmed, per Rule 17(B), after which the red headlight will be extinguished.

The use of the red headlight does not in any manner relieve the train or engine men of responsibility for compliance with the provisions of Rules 99 and 102.

4. Lights will not be displayed by night on train order signals on the 3rd, 4th, 5th, 6th, 7th, 8th, 9th, 10th, 11th, 12th, 13th and 14th Subdivisions. Trains will be governed by the day indication of these train order signals.

5. Rule D-97 applies to all divisions.

6. Except in case of fog, storms, or otherwise bad weather, yellow signals may be used, without flagmen, when placed as prescribed by Rule 10(h) to indicate approach to a red signal on 4th, 5th, 6th, 9th, 10th, 11th and 14th Subdivisions, and also in special cases authorized by the superintendent and protected by train order.

7. Rule 606: Emergency Signals are not used at interlockings or drawbridges operated by the Northern Pacific Railway.

8. Test of hand brakes of gas-electric motor cars must be made once each trip. If crew has charge of moving car prior to leaving initial station, test will be made during such movement; otherwise, as soon as possible after leaving initial station. On cars equipped with "Deadman's Control", conductor and engineer will cooperate in making test.

9. Gas-electric motor cars, when handled dead in freight trains, must be behind caboose. Scale test cars must be handled only in local freight trains and placed immediately ahead of the caboose. Cranes or similar machines geared for self propulsion moving on commercial billing, must not be handled in time freight trains.

10. Precautions must be taken on double track to prevent accidents from swinging doors or other loose construction attached to cars or engines. Trains handling logs must stop when being met or passed by passenger trains.

11. Electric Switch Locks—To operate, open door of electric switch lock and, if indicator shows "proceed", move lock lever to the left, which will unlock switch and permit it to be opened, and movement may be made at once. If indicator shows "stop", and conflicting train movement is not evident, open door of release box and push the push button. This will start operation of clockwork release which will run down in three minutes and, at the end of that time, indicator will show "proceed" and switch can be unlocked by moving lever to the left. Restore lock lever, close and lock doors of electric locks and release boxes when switches are restored to normal position.

12. Signal Operation at Spring Switches Equipped for Switch Key Operation—Unless otherwise provided, the normal position of the spring switch is for main track. The normal indication of main track signals is Proceed. The normal indication of siding signal is Stop. To clear the siding signal when train is ready to enter main track, insert switch key in control box and turn to right. If route is clear the siding signal will immediately clear. If siding signal does not clear by switch key operation, open release box and push the button which will put the time release mechanism into operation. After time release has operated, the siding signal will clear if there is no conflicting train movement. The release box door must be left open until leading wheels of train on the siding have passed the siding signal, then close and lock the release box door. If the siding signal has been cleared and train on the siding is not ready to depart, if necessary to clear signals for a main track movement, open the release box door and push the button which will start the time release mechanism. After the time release mechanism has started to operate, close and lock the release box door.

13. Manual interlockings— Engine whistle signals:
For main track, eastward or westward.....1 long.
From main track to diverging route.....1 long, 1 short, 1 long.
From diverging route to main track.....1 long, 1 short.
On double track—when using reverse track
through interlocking limits2 short, 1 long.
From cross over between main tracks
on double track3 short, 1 long.

14. Bulletin Stations—
Dilworth—Yard office, Roundhouse.
Fargo—Conductor's Room, Headquarters Building.
Valley City—Passenger station.
Jamestown—Passenger station, Yard Office, Roundhouse.
Mandan—Yard Office, Roundhouse.
Carrington—Passenger Station.
Esmond—Passenger Station.

15. Standard Time Clocks—
Dilworth—Telegraph Office.
Fargo—Conductors Room, Headquarters Building.
Train Dispatchers Office.
Jamestown—Passenger Station, Yard Office.
Mandan—Telegraph Office. Carrington—Telegraph Office.

16. Watch Inspectors—

MoorheadHenry Neubarth.
FargoE. W. Johnson.
Valley CityG. H. Toring.
JamestownH. G. Pickard.
MandanA. J. Hendrickson. I. T. Larson.
LaMoureWm. Isaacs.
CooperstownAllen's.
CarringtonE. J. Bestgen.
New RockfordA. R. Hawkinson.

FIRST SUBDIVISION. (MAIN LINE)

1. Speed Restrictions— Zone—Between	Maximum Speeds Permitted	
	Freight and mixed	Passenger
Both tracks—		
Bridge O (Gantz) and Fargo	50	65
Fargo and MP 29 (Casselton)	50	75
Westward track—		
MP 29 and MP 39 (west of Magnolia)	50	65
MP 39 and Buffalo	50	75
Eastward track—		
Buffalo and MP 34 (Wheatland)	50	75
MP 34 and MP 29 (Casselton)	50	65
Single track—		
Buffalo and Peak	50	75
Peak and MP 70 (Berea) both lines....	50	65
MP 70 and MP 95 (Bloom)	50	75
Both tracks—		
MP 95 and Jamestown	50	65

Through Fargo and Moorhead, all trains shall be operated at a reasonable speed and with due care.

At West Fargo, engines classes W-3 and W-5 over both legs of wye5 MPH.

Through Casselton40 MPH.
except, passenger trains handled by diesel engines may operate through Casselton at normal speed.

At Valley City between Third and Sixth Avenues, all trains shall be operated at a reasonable speed and with due care.

2. Bridge and Engine Restrictions—

Bridge 64, Valley City viaduct35 MPH.
Bridge 65.3 on Mill spur, Valley City, not safe for an engine.

At Dilworth and Koldok, engines must not pass over coal dock hopper.

At Dilworth, all A classes and heavier engines entering round house will use middle track and when leaving will use middle or north track.

At Dilworth, engines class W-3 and heavier, not permitted on Gantz pump-house spur.

At Dalrymple, engines class W-3 and heavier not permitted on spur.

At Valley City, engines class W-3 and heavier not permitted on wye or transfer track.

At Jamestown, be governed by Second Subdivision restrictions. Engines, all A classes and heavier, are permitted to use all main line sidings and the following industry and yard tracks only:

At Dilworth, wye and middle or north round house tracks.

Westbound yard, 1 to 6 inc. 9 and north lead.

Eastbound yard, 1 to 9 inc. and south lead.

At Moorhead, G. N. Transfer track.

At Fargo, run-around, short four, yard tracks 5, 6 and 7, except over scale.

West yard tracks 1, 2, 3 and wye.

At West Fargo, to clearance points on east and west leg of wye and on east and west end of house track.

At Union Yard, all tracks.

At Casselton, G. N. Transfer track.

At Wheatland, storage track.

At Valley City, stock yard track.

At Berea, storage tracks 1 and 2.

3. At Fargo, when westward main track is blocked between Broadway and 8th St., the run-around track may be used, leaving main line switches and switches for short four, lined for run-around track.
During the time Trains 187 and 189 are loading, second class and inferior westward trains and yard engines will use run-around track.
Switch leading to Third Subdivision is electrically locked.
4. At West Fargo, trains setting out stock at Armour's must not block south chute of stock yard north of plant. Armour & Company close the gates at their plant each night which are locked with a standard switch lock. Any operation in or out of the plant must be closely watched to avoid breaking or damaging gates.
5. At Fife, trains may expect to find siding blocked at all times.
6. At Buffalo, the normal position of double track switch is for eastward track. Operators will handle.
This switch is equipped with electric lock.
7. At Peak and Berea, the normal position of switches is for route via High Bridge. Operators will handle junction switches and other switches adjacent to their offices. Unless otherwise directed by train order, extra trains will run via High Bridge. Trains running via Valley City will call for route with one long, one short and one long sound of whistle.
8. At Peak, junction switch is equipped with electric lock. Westward trains passing signal 555 at Oriska, and eastward trains passing signal 648 at Valley City, or signal 652 at High Bridge, lock the switch, and if necessary to change the route time release must be used. Instructions for operation of electric lock and time release are posted in station.
9. At Berea, junction switch is equipped with electric lock. Westward trains passing signal 669 west of High Bridge, or signal 675 west of Valley City, and eastward trains passing signal 772 at Sanborn, lock the switch, and if necessary to change route time release must be used. Instructions for operation of electric lock and time release are posted in station.
10. At Urbana, an overlap sign has been placed 1700 feet west of MP 85 on north side of main track. Eastward trains passing this sign will set all westward automatic block signals in stop position as far east as west switch at Eckelson.
11. At Bloom, switch at end of double track is automatically operated dual control switch. Normal position is for westward track.
12. At Jamestown, Second Subdivision Instructions Govern.
13. Spring Switches—
Sanborn, at east end eastward siding, equipped with facing point lock and switch key signal operation.
Eckelson, west end siding, equipped with facing point lock and switch key signal operation.
14. Sidings—
At Valley City, trains taking siding will pull in at first switch. Crossover switch just west of 9th Avenue is the west switch of eastward siding.
Crossover switch just west of 4th Avenue is west switch of westward siding.
At Sanborn, south siding is eastward; north siding is westward.
At Spiritwood, north siding is eastward; south siding is westward.
15. Pusher Districts—Between Koldok and Berea, via Valley City; between Jamestown and Bloom.
16. Yard Limits—The tracks between yard limit signs west of Milwaukee Crossing at Fargo and east of Bridge O, east of Dilworth, will be operated as one yard.
17. Clearance of Structures—The following overhead bridges will not clear man on top of tender of engines Classes A, piled high with coal:
2017 feet west of MP 63 (Low Line) between Peak and Valley City.
1586 feet west of MP 70 (Main track and siding) Berea.
18. Register Stations—
Dilworth.
Fargo—For first class trains and passenger extras.
Casselton—For trains to and from 4th Subdivision.
Valley City—For trains originating and terminating, helper and switch engines.
Sanborn—For trains to and from 5th Subdivision.
Jamestown.

19. Register Exceptions—
Dilworth—Through passenger trains will register by Form 608.
20. Clearance Exceptions—
At Dilworth, trains destined Third Subdivision will require clearance for First and Third Subdivisions.
At Fargo, all first class trains and passenger extras must obtain clearance. Trains from Third Subdivision will not require clearance.

SECOND SUBDIVISION.

(MAIN LINE)

1. Speed Restrictions—
Zone—Between
Jamestown and MP 100 (Eldridge)
Eastward track 50 65
Westward track 50 75
MP 100 and MP 194 (Bismarck) 50 75
MP 194 and Mandan 50 60
At Bismarck, over street crossings,
3rd Street to 12th Street inc. 15 20
At Mandan, westward first class trains, between underpass at Sixth Avenue N. E., and passenger station Restricted speed.
2. Bridge and Engine Restrictions—
When engines Classes A-2 to A-5 inc. or Z-5 to Z-8 inc. are double headed and the second engine is of this class, the engineer of the leading engine will work no steam, or a very little if necessary to do so to keep train moving, while the second engine is on the first curve east of the Missouri River Bridge.
At Jamestown, engines class W and heavier not permitted on Mill Spur beyond Game's Coal Shed.
At Dawson, engines must not pass over coal dock hopper.
At Bismarck, engines Class W and heavier not permitted on Gas Co. spur. Engines heavier than class T-1 not permitted on International Harvester Co. spur, mill spur and Standard Oil Co. spur.
Engines, all A classes and heavier, are permitted to use all main line sidings and the following industry and yard tracks only:
At Jamestown, yard tracks 1 to 6 inc. and 15. Switching leads at east and west end of yard.
Through engine track between coal dock and west end of yard.
Roundhouse tracks, except south out going roundhouse track over and east of blow off pit, and cross over from incoming roundhouse track to through engine track west of coal dock.
Engine lead between roundhouse tracks and passenger station (south bridge track).
North spur west of passenger station.
Run around track 3.
Devils Lake Branch main track within yard limits.
JR&O main track within yard limits and wye.
Other yard tracks may be used when side clearance permits, but only as directed by the yardmaster.
At Bismarck, yard tracks 1, 4 and ramp track.
3. At Jamestown. First track south of passenger station is westward main track; second track is eastward main track; third track is run-around 3.
Between east switch of caboose track and passenger station First Class Trains of 7th Sub-division will observe Operating Rule 93 the same as is required of Second Class and inferior trains.
When main tracks at passenger station are blocked, run-around 3 will be used, leaving main track switches lined for run-around. Eastward first subdivision freight trains crossing over from yard lead to main track may leave switches lined for crossover. Engine herder on duty 6:30 AM to 10:30 PM daily, except Sunday to line routes as far as practicable for trains.
4. At Eldridge, switch at end of double track is an automatically operated dual control switch. Normal position is for the eastward track.

5. At Tappen—

An overlap sign is located just east of passenger station on north side of main track. Westward trains passing this sign will set all eastward automatic block signals in stop position as far west as the east switch at Dawson.

6. At Dawson, operator will close the west switch of westward siding and the east switch of eastward siding behind trains leaving these sidings.

7. At Bismarck, Whistle signal 14 (1) will not be sounded at street crossings within the city limits, except in case of emergency.

When making station stop eastward trains will stop so engine is just west of 5th Street crossing. Westward trains will stop so engine is just east of 3rd Street crossing.

8. At Mandan—

When regular passenger trains meet, the eastward train will, unless otherwise instructed, use the passenger siding. When an eastward passenger train using the passenger siding is at the station when a westward passenger train arrives, the westward train will stop with its engine opposite the engine of the eastward train and not proceed until proceed signal is given by conductor of the eastward train or the yardmaster. If an eastward passenger train is approaching the passenger station and has not come to a stop, westward passenger trains will stop east of the east switch of the passenger siding and remain until the eastward train is stopped.

Yellowstone Division instructions govern.

9. Spring Switches—

Jamestown, at west end yard westward main track switch to yard, not equipped with facing point lock. The normal position is for yard lead.

Before making movement over this spring switch by trains or engines making eastward movement from main track into yard, the switch must be examined to make certain it is properly lined, locked or secured, and that points fit.

Sterling, at east end of siding, equipped with facing point lock and switch key signal operation.

Pierce, at east end of siding, equipped with facing point lock and switch key signal operation.

10. Sidings—

Windsor, north siding is westward; south siding is eastward.

Medina, north siding is eastward; south siding is westward.

Crystal Springs, north siding is eastward, south siding is westward.

Dawson, north siding is eastward; south siding is westward.

Steele, north siding is westward; south siding is eastward.

Burleigh, north siding is westward; south siding is eastward.

At Mandan, the first track south of passenger station is the main track, the second track is passenger train siding.

11. Clearance of Structures—Overhead Bridge, 4681 feet west of MP 124, three and one fourth miles west of Medina, will not clear man on top of tender of engines Classes A, piled high with coal.

12. Pusher Districts. Between Jamestown and Windsor, and between Mandan and Bismarck.

On eastward freight trains out of Mandan with helper or pusher engine going through to Bismarck, conductor in charge of helper will accompany train and helper to Bismarck. When helper engine is on head end, the helper engine will go through to Bismarck.

When the helper engine is to return to Mandan without going through to Bismarck, the conductor of the helper engine will handle the east switch Mandan yard, close it behind the train being helped, which need not come to a stop, and remain at the east switch, holding all other eastward engines and trains until helper engine returns.

13. Register Stations—

Jamestown.

Mandan.

THIRD SUBDIVISION.

(FARGO AND SOUTHWESTERN BRANCH)

- Speed Restrictions—**

Zone—Between	Maximum Speeds Permitted	
	Engine Classes W or heavier	Q4, T and lighter
Fargo and LaMoure	30	40
LaMoure and Edgeley	25	30
Edgeley and Streeter	20	25
- Bridge and Engine Restrictions—**
Engines heavier than Class W-2 not permitted between Fargo and Streeter, except engines class W-5 permitted between La Moure and Independence.
At La Moure engines must not pass over coal dock hopper.
- At Fargo—**Switch leading to First Subdivision is electrically locked.
- At Davenport—**
When agent not on duty route will be lined for Great Northern, when needed for Northern Pacific trains, agent will be called.
- At Independence,** trains may expect to find east leg of wye blocked with cars.
- At La Moure,** trains may expect to find west leg of wye blocked with cars.
- At Edgeley Junction,** normal position of switch is for Streeter branch.
Extra trains will not run via Edgeley unless instructed by train order to do so.
- Doubling Tracks:**
5 miles west of La Moure, capacity 14 cars, switch at west end.
- Register Stations.**
Independence. La Moure. Streeter.
- Clearance Exceptions—**At Fargo, trains from First Subdivision will not require clearance. At Independence, trains from Sixth Subdivision will not require clearance.

FOURTH SUBDIVISION.

(CASSELTON BRANCH)

- Speed Restrictions—**

Zone—Between	Maximum Speeds Permitted	
	Freight and mixed	Passenger
Casseltown and Marion	25	30
- Bridge and Engine Restrictions—**Engines heavier than Class Q-4 not permitted.
- At Casseltown—**Train order signal does not govern Fourth Subdivision trains.
- Register Stations—**
Casseltown. Marion.

FIFTH SUBDIVISION.

(COOPERSTOWN BRANCH)

- Speed Restrictions—**

Zone—Between	Maximum Speeds Permitted	
	Freight and mixed	Passenger
Sanborn and MP 31 (between Hannaford and Shepard)	25	30
MP 31 and passenger station McHenry	40	40
- Bridge and Engine Restrictions—**Engines heavier than Class Q-4 not permitted.
- At Sanborn—**Train order signal does not govern Fifth Subdivision trains.
Yard limit sign does not apply on First Subdivision.
- At Hannaford—**G. N. Agent will handle interlocking plant.
- Register Stations—**
Sanborn. McHenry.

SIXTH SUBDIVISION.

(JAMES RIVER AND OAKES BRANCH)

- Speed Restrictions—**
Maximum Speeds Permitted
Zone—Between
Freight and mixed Passenger
Jamestown and Oakes, 35 40
except, Jamestown and yard limit
sign, Engines Class Z 3 15 MPH.
At Oakes, all trains, over street crossing between freight house
and passenger station 10 MPH.
At Oakes, Chicago and Northwestern Railway and Northern Pa-
cific Railway trains and engines have no time-table superiority
and must proceed at Restricted Speed, within yard limits.
- Bridge and Engine Restrictions—**Engines heavier than Class W-5
not permitted, except Class Z-3 permitted between Jamestown
and yard limit sign.
- At La Moure,** trains may expect to find west leg of wye blocked
with cars.
- At Independence,** trains may expect to find east leg of wye
blocked with cars.
- Pusher District.** Between Jamestown and one and one-half miles
east.
- Register Stations—**
Jamestown. La Moure. Independence. Oakes.

SEVENTH SUBDIVISION.

(DEVILS LAKE BRANCH)

- Speed Restrictions—**
Maximum Speeds Permitted
Zone—Between
Freight and mixed Passenger
Jamestown and Leeds 30 40 45
Engines Classes W-3 or W-5 30
Engines Classes W, W-1 and
W-2 35 35
Except,
Jamestown and Parkhurst—
Eastward trains 25
Engines class Z-3 20
At Carrington, between First St. South and Second St. North,
all trains 25 MPH.
At Leeds, on G. N. transfer track 4 MPH.
At Pingree, between passenger station and 1000 feet west of
8th Subdivision junction switch; at Carrington, between passen-
ger station and Soo line crossing; at Oberon, between passenger
station and 1000 feet west of west wye switch;
First class trains Restricted Speed.
- Bridge and Engine Restrictions—**
Engines heavier than Class W-5 not permitted, except Class Z-3
permitted between Jamestown and Parkhurst.
At Carrington engines must not pass over coal dock hopper.
- At Jamestown,** between east switch of caboose track and pas-
senger station, first class trains of the seventh subdivision will
observe Operating Rule 93 the same as is required of second
class and inferior trains.
- Register Stations—**
Jamestown. Carrington. Oberon. Leeds.
Pingree for first class trains.
- Clearance Exceptions—**
At Pingree, trains from 8th subdivision will not require clearance
if train order signal indicates proceed.
- Pusher District** between Jamestown and Parkhurst.

10

EIGHTH SUBDIVISION.

(WILTON BRANCH)

- Speed Restrictions—**
Maximum Speeds Permitted
Zone—Between
Freight and mixed Passenger
Pingree and Wilton
Engines Classes W-3 or W-5.. 30 40 45
Engines
Classes W, W-1 and W-2.... 35 40
Except,
Pingree and Woodworth, east-
ward 25
 - Bridge and Engine Restrictions—**Engines heavier than Class W-5
not permitted.
At Wilton, bridge over cattle pass, mine spur, must not be used
by Northern Pacific engines.
 - Register Stations—**
Pingree. Wilton.
 - Register Exceptions—**At Pingree trains may register by Form
608 if operator is on duty.
 - Clearance Exceptions—**At Pingree, trains from Seventh Sub-
division will not require clearance if train order signal indicates
proceed.
- TELEPHONE CALLS—**
- | | | | |
|--|---|---|---|
| Jamestown, Trainmasters' Office | 0 | 0 | 0 |
| Jamestown, Freight Office | — | — | — |
| Jamestown, Ticket Office | — | 0 | — |
| Jamestown Yard Office | — | 0 | 0 |
| Jamestown, Yard Telegraph Office | — | 0 | — |
| Jamestown, Roadmasters' Office | — | 0 | 0 |
| Buchanan | — | 0 | 0 |
| Pingree | — | 0 | 0 |
| Goldwin Gravel Pit | — | — | — |
| Woodworth | — | 0 | — |
| Pettibone | — | — | 0 |
| Lake Williams | — | — | — |
| Robinson | — | 0 | 0 |
| Tuttle | — | — | 0 |
| Wing | — | 0 | — |
| Regan | — | — | 0 |
| Wilton | — | — | 0 |

NINTH SUBDIVISION.

(SYKESTON BRANCH)

- Speed Restrictions—**
Maximum Speeds Permitted
Zone—Between
Freight and mixed Passenger
Carrington and Sykeston
Engines Classes W, W-1 and W-2 20 20
Engines Classes Q-4 and lighter.... 25 35
Sykeston and Denhoff
Engines Classes W-2 and lighter 30 35
Denhoff and Turtle Lake
Engines Classes W, W-1 and W-2 20 20
Engines Classes Q-4 and lighter.... 25 35
- Bridge and Engine Restrictions—**Engines heavier than Class W-2
not permitted.
- Register Stations—**
Carrington. Turtle Lake.

TENTH SUBDIVISION.

(OBERON BRANCH)

- Speed Restrictions—**
Maximum Speeds Permitted
Zone—Between
Oberon and Esmond 25
At Oberon, on wye tracks 6
- Bridge and Engine Restrictions—**Engines heavier than Class Q-4
not permitted.
- Register Stations—**
Oberon. Esmond.

11

ELEVENTH SUBDIVISION.

(LINTON BRANCH)

1. Speed Restrictions—

Zone—Between	Maximum Freight and mixed	Passenger
McKenzie and Temvik	40	40
Temvik and Linton	30	30
2. Bridge and Engine Restrictions—Engines heavier than Class W-2 not permitted.
3. At McKenzie—Train order signal does not govern 11th Subdivision trains.
Yard limit sign does not apply on Second Subdivision.
4. Register Stations—
McKenzie. Linton.

TWELFTH SUBDIVISION.

(MANDAN SOUTH LINE)

1. Speed Restrictions—

Zone—Between	Maximum Freight and mixed	Passenger Steam	Motor
Junction switch and MP 5 (west of Cannon Ball)	35	35	40
MP 5 and MP 9	25	25	25
MP 9 and Mott	35	35	40
2. Bridge and Engine Restrictions—Engines heavier than Class W-5 not permitted.
3. At Mandan—All trains will protect against Second Subdivision trains between Passenger Station and Junction Switch.
4. At Cannon Ball Junction—Extra trains will not run via Cannon Ball unless instructed by train order to do so. Normal position of east wye switch is for Mott branch.
5. Register Stations—
Mandan. Mott.

THIRTEENTH SUBDIVISION.

(MANDAN NORTH LINE)

1. Speed Restrictions—

Zone—Between	Maximum Freight and mixed	Passenger Steam	Motor
Junction switch and Kildeer	25	35	40
Engines Classes W-3 or W-5	25	35	
Engines lighter than class W-3	30	35	
2. Bridge and Engine Restrictions—Engines heavier than Class W-5 not permitted.
At Hazen, engines, Class W-3 or heavier, not permitted on Hazen Grain Elevator Track.
Engines must not pass over coal dock hopper.
At Beulah, engines must not pass under tipple tracks 2, 3 and 4 nor go farther than west switch of cross-over west of tipple.
At Republic, engines must not pass under tipple nor go beyond tipple on No. 4 track.
3. At Mandan—All trains will protect against Second Subdivision trains between Passenger Station and Junction Switch.
4. At Beulah, switch leading from west end No. 1 storage track to mine lead shows clear when set for lead.
West switch of cross-over from main track to No. 1 mine storage track must be left set and locked for storage track.
Private crossing 476 feet east of storage track switch and first crossing east of depot must not be blocked.
Examine all inside switches on mine tracks before using.
5. At Hazen, engine fires will not be cleaned or ash pan dumped while taking coal at coal dock.
6. Clearances of structures at following locations are not standard and will not clear a man on top and/or on side of car.
At Beulah, Knife River tipple and three car pullers between tipple tracks east and west end tipple. Slack bin over track 4.
At Republic, Dakota Collieries tipples.
At Zap, loading dock on house track.

7. Clearance Exceptions—At Hazen, trains from Fourteenth Subdivision will not require clearance if train order signal indicates proceed.

8. Register Stations—
Mandan. Zap. Killdeer.

9. Telephone Calls—

Mandan Yard Office	0	0	0
Mandan, Telegraph Office	0	0	0
Mandan, T. M. and R. M. Office	0	0	0
Mandan, Freight Office	0	0	0
Sanger	0	0	0
Price	0	0	0
Hensler	0	0	0
Fort Clark	0	0	0
Stanton	0	0	0
Hazen	0	0	0
Beulah	0	0	0
Zap	0	0	0
Golden Valley	0	0	0
Dodge	0	0	0
Halliday	0	0	0
Werner	0	0	0
Dunn Center	0	0	0
Killdeer	0	0	0

FOURTEENTH SUBDIVISION

(TRUAX BRANCH)

1. Speed Restrictions—

Zone—Between	Maximum Speeds Permitted
Hazen and Truax	25 MPH.
With engines classes W-3 or W-5	25 MPH.
With lighter classes engines	30 MPH.
2. Bridge and engine restrictions—
Engines heavier than class W-5 not permitted.
At Truax, engines not permitted over scale or on tipple tracks.
3. Clearance of Structures—
At Truax, Truax-Traer tipples will not clear a man on top and/or on side of car.
4. Retaining Valves—On eastward freight or mixed trains retaining valves must be used on grades, Truax to Hazen; handles to be turned up to low pressure (horizontal) position beginning at head car as follows:
Trains of 8000 tons or over—20 retaining valves.
Trains of 5000 to 8000 tons—15 retaining valves.
Trains of 3000 to 5000 tons—10 retaining valves.
Trains of less than 3000—No retaining valves.
Retaining valve handles must not be turned up until air brakes are all released following the terminal test of brakes at Truax and must be turned down following the stopping of train at the east switch of the east leg of wye at Hazen.
5. Register Stations—
Hazen.
6. Register Exceptions—At Hazen, trains may register by Form 608 if operator is on duty.
7. Clearance Exceptions—At Hazen, trains from Thirteenth Subdivision will not require clearance if train order signal indicates proceed.

Note—Length of load 33 feet.
Heights and widths in table allow 9 inches clearance.

MAXIMUM CLEARANCES

Table is based on open car loading equally divided on either side of center line of car.

LIMIT OF LOAD MEASUREMENT HEIGHT ABOVE TOP OF RAIL

	1' 0" Wide	2' 0" Wide	3' 0" Wide	4' 0" Wide	5' 0" Wide	6' 0" Wide	7' 0" Wide	7' 6" Wide	8' 0" Wide	Max. Height	Max. Width	Governing Structure
First Sub-division.... Dilworth to Jamestown.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	Coal Dock Dawson
Second Sub-division... Jamestown to Mandan.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Third Sub-division.... Fargo to Streeter.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Fourth Sub-division... Casselton to Marion.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Fifth Sub-division.... Sanborn to McHenry.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Sixth Sub-division.... Oakes to Jamestown.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Seventh Sub-division.. Jamestown to Leeds.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Eighth Sub-division... Pingree to Wilton.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Ninth Sub-division.... Carrington to Turtle Lake.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Tenth Sub-division.... Oberon to Esmond.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Eleventh Sub-division. McKenzie to Linton.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Twelfth Sub-division.. Mandan to Mott.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Thirteenth Sub-division Mandan to Killdeer.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Fourteenth Sub-division Hazen to Truax.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	

Note—Length of load 33 feet.

Heights and widths in table allow 9 inches clearance.

MAXIMUM CLEARANCES—Continued.

Table is based on open car loading equally divided on either side of center line of car.

LIMIT OF LOAD MEASUREMENT HEIGHT ABOVE TOP OF RAIL

	8' 6" Wide	9' 0" Wide	9' 6" Wide	10' 0" Wide	10' 2" Wide	10' 6" Wide	11' 0" Wide	11' 6" Wide	Max. Height	Max. Width	Governing Structure
First Sub-division.... Dilworth to Jamestown.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	Coal Dock Dawson
Second Sub-division... Jamestown to Mandan.....	19' 4"	19' 2"	18' 10"	18' 7"	18' 7"	18' 5"	17' 9"	16' 10"	20' 3"	11' 6"	
Third Sub-division.... Fargo to Streeter.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Fourth Sub-division... Casselton to Marion.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Fifth Sub-division.... Sanborn to McHenry.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Sixth Sub-division.... Oakes to Jamestown.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Seventh Sub-division.. Jamestown to Leeds.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Eighth Sub-division... Pingree to Wilton.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Ninth Sub-division.... Carrington to Turtle Lake.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Tenth Sub-division.... Oberon to Esmond.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Eleventh Sub-division. McKenzie to Linton.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Twelfth Sub-division.. Mandan to Mott.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Thirteenth Sub-division Mandan to Killdeer.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	
Fourteenth Sub-division Hazen to Truax.....	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	20' 3"	11' 6"	

This rating is made to govern rating grades only and will in no manner interfere with handling additional tonnage where the grades will permit.

TONNAGE RATING—FREIGHT ENGINES.

SUB-DIVISION	DISTRICT	CLASS OF ENGINE						SUB-DIVISION	DISTRICT	CLASS OF ENGINE			
		A-2, A-3, A-4, A-5		W-3 W-5		Q-1, Q-3, Q-4				W-1 W-2		Q-1, Q-3, Q-4	
		Tons	Car Lm't	Tons	Car Lm't	Tons	Car Lm't			Tons	Car Lm't	Tons	Car Lm't
FIRST— Westward..	Dilworth to Casselton.....	4320	3600	2900	2880	1908	THIRD— Eastward..	Lisbon to Lisbon Spur.....	1500	990	Car Lm't		
	Casselton to Jamestown.....	6000	5000	3950	2430	2250	FOURTH—	Lisbon Spur to Fargo.....	1800	2250	Car Lm't		
FIRST— Eastward..	Jamestown to Buffalo.....	Car Lm't	3000	3000	2250	1035	Westward..	Casselton to Myra.....	1710	1800	Car Lm't		
	Buffalo to Dilworth.....	Car Lm't	3000	3000	2250	1035		Myra to Embden.....	1350	1800	Car Lm't		
THIRD—	Fargo to Woods.....	4320	3600	2900	2880	1908	FOURTH— Eastward..	Embden to Luca.....	2250	1800	Car Lm't		
	Woods to Leonard.....	6000	5000	3950	2430	2250		Luca to Eastedge.....	2700	1350	Car Lm't		
Westward..	Leonard to Lisbon.....	Car Lm't	3000	3000	2250	1035	FIFTH— Westward..	Kathryn to Hastings.....	1980	1350	Car Lm't		
	Lisbon to Independence.....	Car Lm't	3000	3000	2250	1035		Hastings to Marion.....	2250	2250	Car Lm't		
THIRD—	Independence to La Moure.....	4320	3600	2900	2880	1908	FIFTH— Eastward..	Marion to Kathryn.....	1710	1800	Car Lm't		
	La Moure to Berlin Spur.....	6000	5000	3950	2430	2250		Kathryn to Eastedge.....	1350	1800	Car Lm't		
Westward..	Berlin Spur to Edgeley.....	Car Lm't	3000	3000	2250	1035	FIFTH— Westward..	Eastedge to Casselton.....	2700	1350	Car Lm't		
	Edgeley to Streeter.....	Car Lm't	3000	3000	2250	1035		Sauborn to Hannaford.....	1980	1350	Car Lm't		
THIRD—	Streeter to Edgeley.....	4320	3600	2900	2880	1908	FIFTH— Eastward..	Hannaford to Hannaford Spur.....	2250	1800	Car Lm't		
	Edgeley to La Moure.....	6000	5000	3950	2430	2250		Hannaford Spur to McHenry.....	1710	1800	Car Lm't		
Eastward..	La Moure to Independence.....	Car Lm't	3000	3000	2250	1035	FIFTH— Eastward..	McHenry to Shepard.....	1350	1800	Car Lm't		
	Independence to Englevale.....	Car Lm't	3000	3000	2250	1035		Shepard to Hannaford.....	2700	1350	Car Lm't		
Eastward..	Englevale to Lisbon.....	4320	3600	2900	2880	1908	FIFTH— Eastward..	Hannaford to Sanborn.....	1980	1350	Car Lm't		
		6000	5000	3950	2430	2250				2700	1350	Car Lm't	

SUB-DIVISION	DISTRICT	CLASS OF ENGINE										SUB-DIVISION	DISTRICT	CLASS OF ENGINE									
		A-2, A-3, A-4, A-5					W-1, W-2, W-3, W-5							Q-1, Q-3, Q-4									
		Tons	Tons	Tons	W-1	W-2	W-3	W-5	Tons	Tons	Tons			Q-1	Q-3	Q-4							
SECOND— Westward..	Jamestown to Windsor..	4300	3600	3210	3100	2720	NINTH—	Turtle Lake to Denhoff..	2350	2200	1550												
SECOND—	Windsor to Mandan.....	5700	4400	3500	3200	2290	Eastward...	Denhoff to Bowdon.....	3700	3400	2450												
SECOND—	Mandan to Windsor.....	6000	4600	3600	3350	2290	TENTH—	Bowdon to Carrington...	5000	4600	3300												
SIXTH—	Windsor to Jamestown..	Car Lm't	2375	2185	1575	Westward..	Oberon to Esmond.....	1950	1810	1300													
WESTWARD..	Oakes to Independence..	La Moure to Jamestown..	3600	3250	2390	TENTH—	Esmond to Oberon.....	1950	1810	1300													
SIXTH—	La Moure to Jamestown..	Jamestown to Reeves....	2300	1800	1650	Eastward...	McKenzie to Linton....	1000															
Eastward...	Reeves to La Moure....	Independence to Oakes...	4000	3650	2620	ELEV.—	Linton to Hazleton.....	1150															
SEVENTH	Jamestown to Parkhurst..	Parkhurst to Edmunds...	5400	4900	3660	ENTH—	Hazleton to McKenzie...	2700															
Westward..	Edmunds to New Rockford	New Rockford to Leeds...	1810	1440	1330	Westward..	Mandan to Cannon Ball..	3150															
SEVENTH	Leeds to Divide.....	Divide to Jamestown....	3075	2400	2225	TWELFTH	Cannon Ball to Mott....	2550															
Eastward...	Parkhurst to Edmunds...	Edmunds to New Rockford	3450	3200	2290	Westward..	Mott to Mandan.....	4600															
SEVENTH	New Rockford to Leeds...	Leeds to Divide.....	1950	1810	1300	Eastward...	Mandan to Stanton.....	4900															
Eastward...	Divide to Jamestown....	Pingree to Wilton.....	2050	1900	1380	THIR-	Stanton to Golden Valley..	3400															
EIGHTH—	Pingree to Wilton.....	Wilton to Pettibone.....	4000	3650	2650	TEENTH	Golden Valley to Killdeer..	2850															
Westward..	Wilton to Pettibone.....	Pettibone to Woodworth..	2150	1700	1120	TEENTH	Killdeer to Golden Valley..	4600															
SEVENTH	Pettibone to Woodworth..	Woodworth to Pingree...	2850	2400	2300	Eastward...	Golden Valley to Mandan..	5600															
Eastward...	Woodworth to Pingree...	Carrington to Sykeston...	2450	2000	1850	THIR-																	
NINTH—	Carrington to Sykeston...	Sykeston to Turtle Lake..	5000	3800	3520	TEENTH																	
Westward..	Sykeston to Turtle Lake..		3700	3350	2390	Eastward...																	
			2520	2300	1660																		

SUB-DIVISION	DISTRICT	CLASS OF ENGINE			
		W-3 W-5	W- W-2	W	Q-1 Q-3 Q-4
		Tons	Tons	Tons	Tons
FOUR-TEENTH— Eastward...		Car	Limit	
FOUR-TEENTH— Westward..	2600	2100	1900	1400

J. T. STOTLER,
Asst. Supt.

C. H. SCHUTT,
Trainmaster.

C. L. HARDING
Trainmaster.

H. O. WHITTEN,
Trainmaster.

F. M. SCHAUMBURG,
Trainmaster—
Roadmaster.

R. N. ANDERSEN,
Chief Dispatcher.